

TOSHIBA PROGRAMMABLE UNI JUNCTION TRANSISTOR SILICON PLANAR TYPE

TN41A, TN41B



THYRISTOR-TRIGGER, RELAXATION OSCILLATOR, PULSER AND TIMER APPLICATIONS

Unit in mm

- Low Leakage Current : $I_{GAO}=10\text{nA}$ (Max.)
 $I_{GKS}=100\text{nA}$ (Max.)
- High Pulse Output Voltage : $V_O=10\text{V}$ (Typ.)
- Low Peak Current : $I_P=2\mu\text{A}$ (Max.) TN41A ($R_G=1\text{M}\Omega$)
 $I_P=0.15\mu\text{A}$ (Max.) TN41B ($R_G=1\text{M}\Omega$)

MAXIMUM RATINGS

CHARACTERISTIC	SYMBOL	RATING	UNIT
Gate-Cathode Forward Voltage	V_{GKF}	40	V
Gate-Cathode Reverse Voltage	V_{GKR}	-5	V
Gate-Anode Reverse Voltage	V_{GAR}	40	V
Anode-Cathode Voltage	V_{AK}	± 40	V
DC Anode Current (Note 1)	I_T	150	mA
Repetitive Peak Forward Current (1% Duty Cycle)	I_{TM}	1	A
		2	
Non-Repetitive Peak Forward Current ($t_W=10\mu\text{s}$)	I_{TSM}	5	A
DC Gate Current (Note 1)	I_G	± 20	mA
Capacitive Discharge Energy (Note 2)	E	250	μJ
Power Dissipation (Note 1)	P	300	mW
Operating Temperature	T_{opr}	-50~100	$^{\circ}\text{C}$
Junction Temperature	T_j	-50~125	$^{\circ}\text{C}$
Storage Temperature Range	T_{stg}	-50~125	$^{\circ}\text{C}$



1. ANODE
2. GATE
3. CATHODE

JEDEC	TO-92
EIAJ	SC-43
TOSHIBA	13-5A1C

Weight : 0.2g

961001EAA1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	FIGURE No. AND CONDITION	TN41A			TN41B			UNIT
				MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
Peak Current (V _S = 10V)	R _G = 1MΩ	I _P	1, 2, 3	—	0.05	2	—	0.01	0.15	μA
	R _G = 10kΩ			—	1.0	5	—	0.35	1.0	
Offset Voltage (V _S = 10V)	R _G = 1MΩ	V _T	1, 2, 3	0.2	0.35	1.6	0.2	0.35	0.6	V
	R _G = 10kΩ			0.2	0.45	0.6	0.2	0.45	0.6	
Valley Current (V _S = 10V)	R _G = 1MΩ	I _V	1, 2, 3	—	15	50	—	7	25	μA
	R _G = 10kΩ			70	200	—	25	160	—	
Gate-Anode Leakage Current		I _{GAO}	4, V _S = 40V	—	0.03	10	—	0.03	10	nA
Gate-Cathode Leakage Current		I _{GKS}	5, V _S = 40V	—	0.3	100	—	0.3	100	nA
Forward Voltage		V _F	I _F = 50mA	—	1	1.5	—	1	1.5	V
Pulse Output Voltage		V _O	6, 7	6	10	—	6	10	—	V
Pulse Voltage Rise Time		t _r	6, 7	—	70	80	—	70	80	ns

(Note 1) Derate linearly current and powers 1%/°C above 25°C.

(Note 2) E = 0.5 · CV² capacitor discharge energy limiting resistor and repetition.




Fig.1 Programmable UJT with program resistor R₁ and R₂




Fig.2 Equivalent test circuit for figure 1 used for electrical characteristic testing

$$R_G = \frac{R_1 \cdot R_2}{R_1 + R_2}$$
$$V_S = \frac{R_1}{R_1 + R_2} V$$




Fig.3 V-I electrical characteristics




Fig.4 IGAO test circuit




Fig.5 IGKS test circuit




Fig.6 V_O and t_r test circuit




Fig.7 Waveform of V_O and t_r

